



# A NEW STANDARD IN AREA LIGHTING

Our latest LED area lights are engineered for the highest performance in multiple applications!

Built rugged using die cast aluminum and impact resistant lenses, these IP65 fixtures are all-weather tough. Offered in a type III distribution from 100W-300W, in 4000K & 5000K and in three voltage packages; 100-277V, 100V-347V, & 277-480V, these area lights are built to meet a vast number of applications.









## **TYPE III**

The type III distribution is meant for roadway lighting, general parking areas and other areas where a larger area of lighting is required.



Accessories include direct pole mounts, universal mounts, yoke and trunnion mounts.


Also offered is a unique fixed arm mount or articulating extended slip-fitter with integrated junction boxes that feature sensor knockouts to ease installation (see page 4). Available sensors and controls include photocells, PIR sensors and microwave sensors. Cutoff shields are also available to eliminate light trespass as well as additional 10KV surge protection accessories.

Each maintenance-free area light comes complete with a 2 3/8" slip-fitter mount standard.





### **Dimensional**



## **Photocells, Sensors & Surge Suppression Accessories:**

• 86/221: Photocell For 100-277V Versions

• **86/223**: Photocell For 277-480V Versions

• 86/227: PIR Sensor 100-277V

• 86/228: MW Sensor 100-277V

• 86/226: 12-24V PIR Sensor 277-480V

• **86/224**: 10KV Surge Suppressor 100-277V

• **86/225**: 10KV Surge Suppressor 277-480V

[For additional mounting options see page 7]












ITEM	DESCRIPTION	w	v	сст	LM	DIMENSIONS
65/840	100W LED AREA LIGHT TYPE III	100W	100-277V	4000K	13793	L:20.71" W:12.40" H:3.11"
65/841	100W LED AREA LIGHT TYPE III	100W	100-277V	5000K	13793	L:20.71" W:12.40" H:3.11"
65/842	150W LED AREA LIGHT TYPE III	150W	100-277V	4000K	19507	L:20.71" W:12.40" H:3.11"
65/843	150W LED AREA LIGHT TYPE III	150W	100-277V	5000K	19736	L:20.71" W:12.40" H:3.11"
65/850	100W LED AREA LIGHT TYPE III	100W	100-347V	4000K	13793	L:20.71" W:12.40" H:3.11"
65/851	100W LED AREA LIGHT TYPE III	100W	100-347V	5000K	13793	L:20.71" W:12.40" H:3.11"
65/852	150W LED AREA LIGHT TYPE III	150W	100-347V	4000K	19507	L:20.71" W:12.40" H:3.11"
65/853	150W LED AREA LIGHT TYPE III	150W	100-347V	5000K	19736	L:20.71" W:12.40" H:3.11"
65/860	100W LED AREA LIGHT TYPE III	100W	277-480V	4000K	13793	L:20.71" W:12.40" H:3.11"
65/861	100W LED AREA LIGHT TYPE III	100W	277-480V	5000K	13793	L:20.71" W:12.40" H:3.11"
65/862	150W LED AREA LIGHT TYPE III	150W	277-480V	4000K	19507	L:20.71" W:12.40" H:3.11"
65/863	150W LED AREA LIGHT TYPE III	150W	277-480V	5000K	19736	L:20.71" W:12.40" H:3.11"





### **Dimensional**



# Photocells, Sensors & Surge Suppression Accessories:

• **86/221**: Photocell For 100-277V Versions

• 86/223: Photocell For 277-480V Versions

• 86/227: PIR Sensor 100-277V

• 86/228: MW Sensor 100-277V

• 86/226: 12-24V PIR Sensor 277-480V

• **86/224**: 10KV Surge Suppressor 100-277V

• 86/225: 10KV Surge Suppressor 277-480V

[For additional mounting options see page 8]














ITEM	DESCRIPTION	w	v	сст	LM	DIMENSIONS
65/844	200W LED AREA LIGHT TYPE III	200W	100-277V	4000K	26051	L:22.40" W:14.40" H:3.11"
65/845	200W LED AREA LIGHT TYPE III	200W	100-277V	5000K	26536	L:22.40" W:14.40" H:3.11"
65/854	200W LED AREA LIGHT TYPE III	200W	100-347V	4000K	26051	L:22.40" W:14.40" H:3.11"
65/855	200W LED AREA LIGHT TYPE III	200W	100-347V	5000K	26536	L:22.40" W:14.40" H:3.11"
*65/864	200W LED AREA LIGHT TYPE III	200W	277-480V	4000K	26051	L:30.28" W:12.39" H:3.11"
*65/865	200W LED AREA LIGHT TYPE III	200W	277-480V	5000K	26536	L:30.28" W:12.39" H:3.11"

<sup>\* 277-480</sup>V 200W versions have the same footprint as the 240W & 300W to accommodate the larger drivers.





### **Dimensional**



# Photocells, Sensors & Surge Suppression Accessories:

• 86/221: Photocell For 100-277V Versions

• 86/223: Photocell For 277-480V Versions

• 86/227: PIR Sensor 100-277V

• 86/228: MW Sensor 100-277V

• **86/226**: 12-24V PIR Sensor 277-480V

• **86/224**: 10KV Surge Suppressor 100-277V

• **86/225**: 10KV Surge Suppressor 277-480V

[For additional mounting options see page 9]













ITEM	DESCRIPTION	w	v	сст	LM	DIMENSIONS
65/846	240W LED AREA LIGHT TYPE III	240W	100-277V	4000K	31481	L:30.28" W:12.39" H:3.11"
65/847	240W LED AREA LIGHT TYPE III	240W	100-277V	5000K	32585	L:30.28" W:12.39" H:3.11"
65/848	300W LED AREA LIGHT TYPE III	300W	100-277V	4000K	39815	L:30.28" W:12.39" H:3.11"
65/849	300W LED AREA LIGHT TYPE III	300W	100-277V	5000K	38988	L:30.28" W:12.39" H:3.11"
65/856	240W LED AREA LIGHT TYPE III	240W	100-347V	4000K	31481	L:30.28" W:12.39" H:3.11"
65/857	240W LED AREA LIGHT TYPE III	240W	100-347V	5000K	32585	L:30.28" W:12.39" H:3.11"
65/858	300W LED AREA LIGHT TYPE III	300W	100-347V	4000K	39815	L:30.28" W:12.39" H:3.11"
65/859	300W LED AREA LIGHT TYPE III	300W	100-347V	5000K	38988	L:30.28" W:12.39" H:3.11"
65/866	240W LED AREA LIGHT TYPE III	240W	277-480V	4000K	31481	L:30.28" W:12.39" H:3.11"
65/867	240W LED AREA LIGHT TYPE III	240W	277-480V	5000K	32585	L:30.28" W:12.39" H:3.11"
65/868	300W LED AREA LIGHT TYPE III	300W	277-480V	4000K	39815	L:30.28" W:12.39" H:3.11"
65/869	300W LED AREA LIGHT TYPE III	300W	277-480V	5000K	38988	L:30.28" W:12.39" H:3.11"




Lumiled 2835R Chips & Advanced Optics for Superior Performance

# **Special Features**

High performance meets rugged, all weather tough, design. Using high quality build materials such as Lumileds chips and Sosen drivers, these fixtures are built to last. Advanced thermal consideration and heat dissipation is at the core of the design. Engineered with integrated respirators to balance air pressure, integrated 4KV surge protection, and seismically 3G vibration tested, there is not much these fixtures cannot handle.


Offering a full suite of mounting accessories including innovative extended slip-fitter and fixed arm mounts with integrated junction boxes; photocells, PIR & MW sensors, additional add on surge suppression and cutoff shields, these fixtures will meet the needs of any type III application.





## **Integrated Respirator**

Integrated respirators help to balance air pressure and prevent humidity build-up.



## Finned, Heat Sink Design


Finned, Heat Sink Design allows for better performance and heat dissipations.



## Slip-Fitter Adjustable Mounting

Fixtures come standard with a 2 3/8" slip-fitter adjustable mount with 90 degree up or down articulation.

## HEAVY DUTY HARDWARE & DIE-CASTING, A RUGGED BUILD TO WITHSTAND HARSH OUTDOOR ENVIRONMENTS •







# Mounting Options & Accessories

A full suite of mounting accessories and add-on sensors are available for the needs of multiple applications.

All fixtures include 2 3/8" Slip-Fitter Standard.



Extended Slip-Fitter Mount with Sensor Knockouts 65/875



Universal Mount with 2 3/8" Slip-Fitter Mount or Direct Mount for Square & round Poles 65/870



Direct Mount for Square & Round Poles. 65/871



Trunnion 65/872




Yoke 65/873 & 65/874



\*Cutoff Shield 65/877 & 65/878



# Innovative Mounting Accessories with Knockouts & Integrated Junction Boxes For Greater Ease Of Installation





ITEM#	DESCRIPTION	FEATURE	PK
65/870	UNIVERSAL MOUNT	DIRECT & SLIP-FITTER MOUNT BRONZE	8
65/871	DIRECT MOUNT	SQUARE/ROUND POLE MOUNT BRONZE	8
65/872	TRUNNION MOUNT	BRONZE FINISH	8
65/873	YOKE MOUNT	100W/150W/200W BRONZE	8
65/874	YOKE MOUNT	240W/300W BRONZE	8
65/875	EXT SLIP-FITTER	WITH SENSOR KNOCKOUTS BRONZE	8
65/876	FIXED ARM MOUNT	WITH SENSOR KNOCKOUTS BRONZE	8
65/877	CUTOFF SHIELD	BRONZE - 100W/150W/240W/300W & 200W 277-480V	8
65/878	CUTOFF SHIELD	BRONZE - 200W 100-277V & 100-347V	8
86/221	PHOTOCELL/SOCKET	100-277V FOR 100W/200W	50
86/222	PHOTOCELL/SOCKET	100-277V FOR 240W/300W	50
86/223	PHOTOCELL/SOCKET	277-480V	50
86/224	SURGE SUPPRESSOR	10KV - 100-277V	50
86/225	SURGE SUPPRESSOR	10KV - 277-480V	50
86/226	12-24V PIR SENSOR	277-480V	50
86/227	PIR SENSOR	100-277V	50
86/228	MICROWAVE SENSOR	100-277V	50

# **Product Dimensions with Alternate Mounting Options**


### 100W&150W

A full assortment of mounting accessories to meet any applications needs.












65/871 Direct Mount




65/872 Trunnion Mount




65/873 Yoke Mount



65/875 Extended 2 3/8" Slip-Fitter with knockouts and integrated junction box.




65/876
Fixed Arm Mount with Knockouts and integrated junction box.




### 200W


Innovative mounting accessories with Knockouts & Integrated Junction Boxes for Greater Ease Of Installation.


\*200W 277-480V have the same footprint as the 240W & 340W Versions to accommodate the larger drivers.




#### 2 3/8" Slip-Fitter (Included)









65/871 Direct Mount




65/872 Trunnion Mount




65/873 Yoke Mount



65/875 Extended 2 3/8" Slip-Fitter with knockouts and integrated junction box.




65/876
Fixed Arm Mount with Knockouts and integrated junction box.




## 240W&300W

(Also 200W 277V-480V)


Cutoff shields are also available to eliminate light trespass.




#### 2 3/8" Slip-Fitter (Included)




65/870 Universal Mount




65/871 Direct Mount




65/872 Trunnion Mount




65/874 Yoke Mount



65/875
Extended 2 3/8" Slip-Fitter with knockouts and integrated junction box.



65/876
Fixed Arm Mount with Knockouts and integrated junction box.







# Product Accessories & Mounting Options Dimensions

## **Cut-Off Shield**

- 65-877 for 100W/150W/240W/300W and 200W 277-480V versions.
- 65-878 for use with 200W 100-277V and 100-347V versions.









# Mounting Accessories


Included 2 3/8" Slip-Fitter



65/870 Universal Mount




65/871 Direct Mount







65/872 Trunnion Mount




65/873 Yoke Mount for use with 100W/150W/200W




65/874 Yoke Mount for use with 240W/300W



65/875
Extended 2 3/8" Slip-Fitter with knockouts and integrated junction box.



65/876
Fixed Arm Mount with Knockouts and integrated junction box.



# **SATCO** NUVO

# A SINGLE SOURCE FOR YOUR LIGHTING NEEDS

We answer today's evolving lighting needs with thousands of products that offer energy efficiency, high quality illumination, value, safety and solutions through innovation and design.

Satco manufactures thousands of lighting solutions.

With products that range from LED lamps and fixtures to traditional lighting and components, stocked at the ready throughout North America, we supply the market.





#### **DISTRIBUTION CENTERS**

#### **New York (Headquarters)**

110 Heartland Blvd., Brentwood, NY 11717

Tel. 631-243-2022, Fax: 631-243-2027

#### **Texas**

2000 Valwood Parkway, Farmers Branch, TX 75234

Tel. 972-247-2437, Fax: 972-247-5408

#### **Florida**

900 N.W. 159th Drive, Miami, FL 33169

Tel. 305-624-2044, Fax: 305-623-0286

#### **California**

31288 San Benito Street, Hayward, CA 94544

Tel. 510-487-4822, Fax: 510-487-8955

#### Washington

4710 116th S.W., Mukilteo, WA 98275

Tel. 425-789-3300, Fax: 425-789-3310

#### **Puerto Rico**

Campech Street. 23 Julio

N. Matos Industrial Park, Carolina, PR 00984

Tel. 787-757-3510, Fax: 787-757-3540

#### Canada & Mexico

Internationalsales@satco.com/631-243-2022 EXT315