SATCO[®] NUVO[®]





CCT SELECTABLE 3000K/4000K/5000K

0-10V DIMMING

INTEGRATED SENSOR PORT

CEILING AND PENDANT MOUNTING

IK08 IMPACT RATED

50,000 FUNCTIONAL LIFE

DLC PREMIUM

SUGGESTED APPLICATIONS Commercial and Industrial

Applications: Garages, Warehouses, Retail



LED ROUND CANOPY LIGHT WITH SENSOR PORT

CCT SELECTABLE



DURABLE, RUGGED AND VERSATILE

SATCO|NUVO's LED Round Canopy Lights are the perfect combination of durability and versatile functionality. With ColorQuick technology, easily select 3000K, 4000K or 5000K color temperatures during installation. Also, these feature an integrated sensor port, providing a convenient option to add a microwave or PIR motion sensor for even more energy savings and enhanced security. Crafted from premium quality die-cast aluminum, these fixtures are IK08 impact rated and designed to withstand the toughest environments. Whether brightening up a parking garage, illuminating a loading dock or adding extra security to your outdoor space, these canopy fixtures are a versatile lighting solution.



GENERAL SPECIFICATIONS

Input Voltage, Frequency: 120-277V, 50/60Hz Construction: Die Cast Aluminum **CCT:** 3000K/4000K/5000K Dimmable: 0-10V Dimming Impact Rating: IK08 Beam Angle: 150° **CRI:** 80

Functional Life: 50,000 Hours Location Rating: Wet, IP65 Ambient Operating Temperature: -40°C (-40°F) to +45°C (+113°F) Mounting Options: Ceiling and Pendant Mounting Warranty: 5 Years

ITEM SPECIFICATIONS / ORDER INFO

Item	UPC	Lumens	Wattage	Efficacy	Surge Protection Rating	Bug Rating	Finish	DLC ID
65-623R1	045923652196	3718L/3975L/3766L	25W	Up to 159 LPW	2.5 kV	B2-U3-G1	White	S-BW0DFO
65-624R1	045923652202	3718L/3975L/3766L	25W	Up to 159 LPW	2.5 kV	B2-U3-G1	Bronze	S-ONXTZB
65-625R1	045923652264	5785L/6215L/5909L	40W	Up to 155LPW	4 kV	B2-U3-G2	White	S-DJS10Y
65-626R1	045923652288	5785L/6215L/5909L	40W	Up to 155 LPW	4 kV	B2-U3-G2	Bronze	S-MUEZYA
65-627R1	045923652295	7733L/8284L/8072L	55W	Up to 151 LPW	4 kV	B3-U3-G2	White	S-EV3ODN
65-628R1	045923652301	7733L/8284L/8072L	55W	Up to 151 LPW	4 kV	B3-U3-G2	Bronze	S-260R9W
65-629R1	045923652387	10887L/11573L/11290L	75W	Up to 154 LPW	6 kV	B3-U3-G2	White	S-SPDV10
65-630R1	045923652394	10887L/11573L/11290L	75W	Up to 154 LPW	6 kV	B3-U3-G2	Bronze	S-27WAZN
65-631R1	045923652400	14298L/15322/14943L	100W	Up to 153 LPW	6 kV	B3-U3-G2	White	S-1JCFE3
65-632R1	045923652851	14298L/15322/14943L	100W	Up to 153 LPW	6 kV	B3-U3-G2	Bronze	S-ZW3LNP

OPTIONAL ACCESSORIES (SOLD SEPARATELY)

Item	UPC	Description	
86-217	045923862175	5 PIR Sensor/6 Meter	
86-220	045923862205	PIR Sensor/12 Meter	
86-218	045923666353	Microwave Sensor	
86-219	045923665967	Sensor Programming Remote	
65-638	045923656385	8W Emergency Backup	
65-639	045923656392	15W Emergency Backup	



PIR Sensor



(86-218)


(86-217 and 86-220)

Microwave Sensor

Remote for 86/218 (86-219)



Emergency Backup





Emergency Function

Item	Fixture Wattage	Charging Time	Emergency Time
65-638	25W/45W/55W	>24 Hours	>90 Minutes
65-639	75W/100W	>24 Hours	>90 Minutes

DIMENSIONS/WEIGHTS

Item	Diameter (A)	Height (B)	Weight (Lbs)
65-623R1	10.04″	3.15″	4.41
65-624R1	10.04″	3.15″	4.41
65-625R1	10.04″	3.15″	4.41
65-626R1	10.04″	3.15″	4.41
65-627R1	10.04″	3.15″	4.41
65-628R1	10.04″	3.15″	4.41
65-629R1	11.02″	3.15″	6.56
65-630R1	11.02″	3.15″	6.56
65-631R1	11.02″	3.15″	6.56
65-632R1	11.02″	3.15″	6.56





This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Fixture may not be compatible with all dimmers

Visit www.satco.com or call 1-800-437-2826 for a list of compatible dimmers. Specifications are subject to change without prior notice.

Visit satco.com/service/warranty for complete 5 year warranty details.

SATCO.COM | 800-437-2826

© Satco Products, Inc. All rights reserved. Rev. 3/24 NU1784