

S11943

23T5/LED/48-840/XD

GENERAL SPECIFICATIONS

Shape: T5 Wattage: 23W 4000K Color Temperature:

48" Length:

Miniature Bi Pin Base:









TECHNICAL SPECIFICATIONS

Wattage:	23W
Volts:	120V-277V
Incandescent Equivalent:	100W
Fluorescent Equivalent:	54W
Shape:	T5
Filament:	LED
Base:	Miniature Bi Pin
ANSI Base:	G5
Finish:	Frost
Hours Rated:	50000H
Color Temperature:	4000K
CRI:	82CRI
Lumen Output:	3400L

Dimmable:	Yes-Dimmable
Dimming Function:	0-10V Dimming Only
Beam Spread:	220D
Power Factor:	0.9
Operating Temp:	-20C (-4F) to +45C (+113F)
Ballasting Requirements:	Ballast replaced with external driver
Bypass / Direct:	Replace with external driver
Ballast Type:	Туре С
Safety Listing:	cULus - Classified; cULus - Certified
Technology:	LED
Material:	Glass

DIMENSIONS

MOL:	48"
MOD:	0.63"
Weight:	0.31

LISTINGS

Safety Listing:	cULus - Classified; cULus - Certified
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PLCXVV6NDZC1
DLC Primary Use:	4-lamp External Driver (UL Type C) Lamps
UL File Listing:	US/CN - E356817
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	ETL Sanitation listed (conforms to NSF)
SDS Class:	LED_Lamp

PACKAGING

Each UPC: 045923119439 Case UPC: 10045923119436 Each Quantity: 1 25 Case Quantity:

Copyright 2024 110 Heartland Blvd. National Toll-Free **Distribution Centers** Brentwood, NY 11717 New York, Florida, 800-43-SATCO Satco Products, Inc. PH 631-243-2022 Texas, Washington, (800-437-2826) All Rights Reserved FX 631-243-2027 California, Puerto Rico www.satco.com May 18, 2024