



## S11989

10.5T8/LED/48-835/BP/USA

### GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	10.5W
Color Temperature:	3500K
Length:	47.78"
Base:	Medium Bi Pin



### TECHNICAL SPECIFICATIONS

Wattage:	10.5W	Beam Spread:	210D
Volts:	120V-277V	Power Factor:	0.9
Incandescent Equivalent:	50W	Operating Temp:	-20C (-4F) to +45C (+113F)
Fluorescent Equivalent:	30W	Ballasting Requirements:	Ballast Bypass
Shape:	T8	Bypass / Direct:	Ballast Bypass
Filament:	LED	Ballast Type:	Type B
Base:	Medium Bi Pin	Single / Dual End:	Single Ended; Double Ended
ANSI Base:	G13	Safety Listing:	cULus - Classified; cULus - Certified; cRUus - Recognized Component
Finish:	Frost	Technology:	LED
Housing Color:	White	Material:	Glass / Plastic
Hours Rated:	50000H		
Color Temperature:	3500K		
CRI:	82CRI		
Lumen Output:	1700L		

### DIMENSIONS

MOL:	47.78"
MOD:	1"
Weight:	0.44

### LISTINGS

Safety Listing:	cULus - Classified; cULus - Certified; cRUus - Recognized Component
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PLFF68VB1ET4
DLC Primary Use:	Internal Driver/Line Voltage (UL Type B) Lamps
UL File Listing:	US/CN - E356817; US/CN - E335148
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

### PACKAGING

Each UPC:	045923119897	Case UPC:	10045923119894
Each Quantity:	1	Case Quantity:	25
Each Dimensions:	48.00 x 1.00 x 1.00"	Case Dimensions:	48.80 x 6.10 x 6.30"
110 Heartland Blvd.	Distribution Centers	National Toll-Free	Copyright 2024
Brentwood, NY 11717	New York, Florida,	800-43-SATCO	Satco Products, Inc.
PH 631-243-2022	Texas, Washington,	(800-437-2826)	All Rights Reserved
FX 631-243-2027	California, Puerto Rico	www.satco.com	December 22, 2024