



S16414

11T8/LED/HO-SIGN/30-840/BP

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	11W
Color Temperature:	4000K
Length:	27.88"
Base:	Recessed Double Contact HO/VHO



TECHNICAL SPECIFICATIONS

Wattage:	11W	Dimmable:	Non-Dimmable
Volts:	120V-277V	Beam Spread:	360D
Incandescent Equivalent:	50W	Power Factor:	0.9
Fluorescent Equivalent:	42W	Operating Temp:	-30C (-22F) to +45C (+113F)
Shape:	T8	Ballasting Requirements:	Ballast Bypass
Filament:	LED	Bypass / Direct:	Ballast Bypass
Base:	Recessed Double Contact HO/VHO	Ballast Type:	Type B
ANSI Base:	R17d	Single / Dual End:	Single Ended
Finish:	Frost	Tube Guard Use:	No
Housing Color:	White	Safety Listing:	cULus - Classified; cULus - Certified; cRUus - Recognized Component; ETLus - SANITATION RECOGNIZED COMPONENT
Hours Rated:	50000H	Technology:	LED
Color Temperature:	4000K	Material:	Plastic
CRI:	83CRI		
Lumen Output:	1500L		

DIMENSIONS

MOL:	27.88"
MOD:	1"
Weight:	0.39

LISTINGS

Safety Listing:	cULus - Classified; cULus - Certified; cRUus - Recognized Component; ETLus - SANITATION RECOGNIZED COMPONENT
Location Rating:	Damp
Energy Star:	No
DLC Approved:	No
UL Application:	Tubes
UL File Listing:	US/CN - E356817; US/CN - E335148; US/CN - E504973
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923164149	Case UPC:	10045923164146
Each Quantity:	1	Case Quantity:	10
Each Dimensions:	30.00 x 1.10 x 1.10"	Case Dimensions:	29.80 x 7.87 x 4.92"

110 Heartland Blvd. Brentwood, NY 11717 PH 631-243-2022 FX 631-243-2027	Distribution Centers New York, Florida, Texas, Washington, California, Puerto Rico	National Toll-Free 800-43-SATCO (800-437-2826) www.satco.com	Copyright 2024 Satco Products, Inc. All Rights Reserved December 22, 2024
--	---	---	--