



S16417

15T8/LED/HO-SIGN/42-865/BP

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	15W
Color Temperature:	6500K
Length:	40"
Base:	Recessed Double Contact HO/VHO



TECHNICAL SPECIFICATIONS

Wattage:	15W	Dimmable:	Non-Dimmable
Volts:	120V-277V	Beam Spread:	360D
Incandescent Equivalent:	75W	Power Factor:	0.9
Fluorescent Equivalent:	55W	Operating Temp:	-30C (-22F) to +45C (+113F)
Shape:	T8	Ballasting Requirements:	Ballast Bypass
Filament:	LED	Bypass / Direct:	Ballast Bypass
Base:	Recessed Double Contact HO/VHO	Ballast Type:	Type B
ANSI Base:	R17d	Single / Dual End:	Single Ended
Finish:	Frost	Tube Guard Use:	Not Approved
Housing Color:	White	Safety Listing:	cULus - Classified; cULus - Certified; cRUus - Recognized Component; ETLus - SANITATION RECOGNIZED COMPONENT
Hours Rated:	50000H	Technology:	LED
Color Temperature:	6500K	Material:	Plastic
CRI:	83CRI		
Lumen Output:	2100L		

DIMENSIONS

MOL:	40"
MOD:	1"
Weight:	0.55

LISTINGS

Safety Listing:	cULus - Classified; cULus - Certified; cRUus - Recognized Component; ETLus - SANITATION RECOGNIZED COMPONENT
Location Rating:	Damp
Energy Star:	No
DLC Approved:	No
UL Application:	Tubes
UL File Listing:	US/CN - E356817; US/CN - E335148; US/CN - E504973
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923164170	Case UPC:	10045923164177
Each Quantity:	1	Case Quantity:	10
Each Dimensions:	42.00 x 1.10 x 1.10"	Case Dimensions:	42.10 x 7.87 x 4.92"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2024
Satco Products, Inc.
All Rights Reserved
May 14, 2024