



S16419

26T8/LED/HO-SIGN/64-865/BP

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	26W
Color Temperature:	6500K
Length:	61.88"
Base:	Recessed Double Contact HO/VHO



TECHNICAL SPECIFICATIONS

Wattage:	26W
Volts:	120V-277V
Incandescent Equivalent:	100W
Fluorescent Equivalent:	80W
Shape:	T8
Filament:	LED
Base:	Recessed Double Contact HO/VHO
ANSI Base:	R17d
Finish:	Frost
Housing Color:	White
Hours Rated:	50000H
Color Temperature:	6500K
CRI:	83CRI
Lumen Output:	3650L

Dimmable:	Non-Dimmable
Beam Spread:	360D
Power Factor:	0.9
Operating Temp:	-30C (-22F) to +45C (+113F)
Ballasting Requirements:	Ballast Bypass
Bypass / Direct:	Ballast Bypass
Ballast Type:	Type B
Single / Dual End:	Single Ended
Tube Guard Use:	No
Safety Listing:	cULus - Classified; cULus - Certified; cRUus - Recognized Component; ETLus - Sanitation Recognized Component
Technology:	LED
Material:	Plastic

DIMENSIONS

MOL:	61.88"
MOD:	1"
Weight:	1.19

LISTINGS

Safety Listing:	cULus - Classified; cULus - Certified; cRUus - Recognized Component; ETLus - Sanitation Recognized Component
Location Rating:	Damp
Energy Star:	No
DLC Approved:	No
UL Application:	Tubes
UL File Listing:	US/CN - E356817; US/CN - E335148; US/CN - E504973
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923164194	Case UPC:	10045923164191
Each Quantity:	1	Case Quantity:	10
Each Dimensions:	64.00 x 1.10 x 1.10"	Case Dimensions:	63.80 x 7.87 x 4.92"

110 Heartland Blvd. Brentwood, NY 11717 PH 631-243-2022 FX 631-243-2027	Distribution Centers New York, Florida, Texas, Washington, California, Puerto Rico	National Toll-Free 800-43-SATCO (800-437-2826) www.satco.com	Copyright 2024 Satco Products, Inc. All Rights Reserved December 22, 2024
--	---	---	--