



S18451

13T8/U1-G13/LED/835/DUAL

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	13W
Color Temperature:	3500K
Length:	22.59"
Base:	Medium Bi Pin



TECHNICAL SPECIFICATIONS

Wattage:	13W	Beam Spread:	160D
Volts:	120V-277V	Power Factor:	0.9
Incandescent Equivalent:	50W	Operating Temp:	-25C (-13F) to +45C (+113F)
Fluorescent Equivalent:	31W	Ballasting Requirements:	Ballast required (Type A) or Ballast Bypass (Type B)
Shape:	T8	Bypass / Direct:	Dual
Filament:	LED	Ballast Type:	Type A/B
Base:	Medium Bi Pin	Single / Dual End:	Single Ended; Double Ended
ANSI Base:	G13	Shatter Proof Type:	Yes
Finish:	Frost	Safety Listing:	cULus - Listed; cULus - Classified; ETLus - SANITATION RECOGNIZED COMPONENT
Housing Color:	White	Technology:	LED
Hours Rated:	50000H	Material:	Plastic
Color Temperature:	3500K		
CRI:	80CRI		
Lumen Output:	1800L		

DIMENSIONS

MOL:	22.59"
MOD:	1"
Leg Spacing:	1.625

LISTINGS

Safety Listing:	cULus - Listed; cULus - Classified; ETLus - SANITATION RECOGNIZED COMPONENT
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard; Standard
DLC ID:	PLIP7GRMDBS6; PLNGZPZ9UOHF
DLC Primary Use:	Replacement Lamps (Plug and Play) (UL Type A); Dual Mode Internal Driver (UL Type A and Type B)
UL File Listing:	CN/US - E335148; CN/US - E356817; ETL - 4005203
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	ETL Sanitation listed (conforms to NSF)
SDS Class:	LED_Lamp

PACKAGING

1 Each UPC: 10045923184519	045923184512	National Toll-Free	Case UPC: Copyright 2024 10045923184519
Each Quantity: 1	1, Florida,	800-43-SATCO	Case Quantity: 24
Each Dimensions: 23.20 x 2.80 x 1.625	Washington,	(800-437-2826)	Case Dimensions: 24.40 x 6.30 x 15.20"
F. , Puerto Rico		www.satco.com	May 1, 2024