



S21407

PLT/16W/V/LED/850/4P/DR

GENERAL SPECIFICATIONS

Shape:	PL
Wattage:	16W
Lumen Output:	1850L
Color Temperature:	5000K
Base:	G24q (4-Pin)



TECHNICAL SPECIFICATIONS

Wattage:	16W	CRI:	82CRI
Volts:	120V-277V	Lumen Output:	1850L
Incandescent Equivalent:	100W	Beam Spread:	110D
Fluorescent Equivalent:	42W	Power Factor:	0.9
Shape:	PL	Operating Temp:	-20C (-4F) to +45C (+113F)
Filament:	LED	Ballasting Requirements:	Ballast required
Base:	G24q (4-Pin)	Safety Listing:	cULus
ANSI Base:	G24q	Technology:	LED
Finish:	Frost		
Housing Color:	White		
Hours Rated:	50000H		
Color Temperature:	5000K		

DIMENSIONS

MOL:	5.19"
MOD:	3.75"
Weight:	0.35

LISTINGS

Safety Listing:	cULus
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PL9E574BZGHJ
DLC Primary Use:	Replacement Lamps (plug and play) (UL Type A)
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923224072	Inner UPC:	20045923224076	Case UPC:	10045923224079
Each Quantity:	1	Inner Quantity:	10	Case Quantity:	20
Each Dimensions:	3.86 x 3.86 x 6.30"	Inner Dimensions:	20.08 x 8.27 x 6.70"	Case Dimensions:	20.86 x 8.86 x 14.17"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2024
Satco Products, Inc.
All Rights Reserved
May 6, 2024