



S29860

9WPLV/LED/840/DR/4P

GENERAL SPECIFICATIONS

Shape:	PL
Wattage:	9W
Lumen Output:	1100L
Color Temperature:	4000K
Base:	G24q (4-Pin)



TECHNICAL SPECIFICATIONS

Wattage:	9W	CRI:	82CRI
Volts:	120V-277V	Lumen Output:	1100L
Incandescent Equivalent:	40W	Beam Spread:	120D
Fluorescent Equivalent:	18W/26W/32W/42W	Power Factor:	0.9
Shape:	PL	Operating Temp:	-20C (-4F) to +45C (+113F)
Filament:	LED	Ballasting Requirements:	Ballast required
Base:	G24q (4-Pin)	Safety Listing:	cULus
ANSI Base:	G24q	Technology:	LED
Finish:	Frost		
Housing Color:	White		
Hours Rated:	50000H		
Color Temperature:	4000K		

DIMENSIONS

MOL:	4.69"
MOD:	1.91"

LISTINGS

Safety Listing:	cULus
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PLZ5IXDQS03
DLC Primary Use:	Replacement Lamps (plug and play) (UL Type A)
UL File Listing:	US/CN E335148
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923298608	Inner UPC:	20045923298602	Case UPC:	10045923298605
Each Quantity:	1	Inner Quantity:	10	Case Quantity:	50
Each Dimensions:	2.00 x 2.00 x 4.80"	Inner Dimensions:	10.00 x 4.17 x 5.12"	Case Dimensions:	11.00 x 10.60 x 10.60"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2024
Satco Products, Inc.
All Rights Reserved
May 7, 2024