



## S29934

12T8/LED/48-830/DR

### GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	12W
Color Temperature:	3000K
Length:	48"
Base:	Medium Bi Pin



### TECHNICAL SPECIFICATIONS

Wattage:	12W	Dimmable:	Non-Dimmable
Volts:	Ballast DependentV	Beam Spread:	210D
Incandescent Equivalent:	60W	Power Factor:	0.9
Fluorescent Equivalent:	25W-32W	Operating Temp:	-20C (-4F) to +45C (+113F)
Shape:	T8	Ballasting Requirements:	Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart
Filament:	LED		
Base:	Medium Bi Pin	Bypass / Direct:	Direct
ANSI Base:	G13	Ballast Type:	Type A
Finish:	Gloss	Safety Listing:	cULus
Hours Rated:	50000H	Technology:	LED
Color Temperature:	3000K		
CRI:	82CRI		
Lumen Output:	1700L		

### DIMENSIONS

MOL:	48"
MOD:	1"

### LISTINGS

Safety Listing:	cULus
Location Rating:	Damp
Energy Star:	No
DLC Approved:	No
UL File Listing:	US/CN E335148
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
SDS Class:	LED_Lamp

### PACKAGING

Each UPC:	045923299346	Case UPC:	10045923299343
Each Quantity:	1	Case Quantity:	10
Each Dimensions:	48.00 x 1.10 x 1.10"	Case Dimensions:	49.60 x 8.30 x 4.30"

110 Heartland Blvd.  
Brentwood, NY 11717  
PH 631-243-2022  
FX 631-243-2027

Distribution Centers  
New York, Florida,  
Texas, Washington,  
California, Puerto Rico

National Toll-Free  
800-43-SATCO  
(800-437-2826)  
www.satco.com

Copyright 2024  
Satco Products, Inc.  
All Rights Reserved  
December 22, 2024