



S29937

12T8/LED/48-850/DR

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	12W
Color Temperature:	5000K
Length:	48"
Base:	Medium Bi Pin



TECHNICAL SPECIFICATIONS

Wattage:	12W	Dimmable:	Non-Dimmable
Volts:	Ballast DependentV	Beam Spread:	210D
Incandescent Equivalent:	60W	Power Factor:	0.9
Fluorescent Equivalent:	25W-32W	Operating Temp:	-20C (-4F) to +45C (+113F)
Shape:	T8	Ballasting Requirements:	Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart
Filament:	LED		
Base:	Medium Bi Pin	Bypass / Direct:	Direct
ANSI Base:	G13	Ballast Type:	Type A
Finish:	Gloss	Safety Listing:	cULus
Hours Rated:	50000H	Technology:	LED
Color Temperature:	5000K		
CRI:	82CRI		
Lumen Output:	1800L		

DIMENSIONS

MOL:	48"
MOD:	1"
Weight:	0.41

LISTINGS

Safety Listing:	cULus
Location Rating:	Damp
Energy Star:	No
DLC Approved:	No
UL File Listing:	US/CN E335148
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923299377
Each Quantity:	1
Each Dimensions:	48.00 x 1.10 x 1.10"

Case UPC:	10045923299374
Case Quantity:	10
Case Dimensions:	49.60 x 8.30 x 4.30"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2024
Satco Products, Inc.
All Rights Reserved
December 22, 2024