



## S39902

9T8/LED/24-840/BP/SE-DE

### GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	9W
Color Temperature:	4000K
Length:	23.78"
Base:	Medium Bi Pin



### TECHNICAL SPECIFICATIONS

Wattage:	9W	Beam Spread:	210D
Volts:	120V-277V	Power Factor:	0.9
Incandescent Equivalent:	40W	Operating Temp:	-20C (-4F) to +45C (+113F)
Fluorescent Equivalent:	17W	Ballasting Requirements:	Ballast Bypass
Shape:	T8	Bypass / Direct:	Ballast Bypass
Filament:	LED	Ballast Type:	Type B
Base:	Medium Bi Pin	Single / Dual End:	Single Ended; Double Ended
ANSI Base:	G13	Tube Guard Use:	Approved for use with tube guards
Finish:	Gloss White	Safety Listing:	cULus - Classified; cRUus - Recognized Component
Housing Color:	White	Technology:	LED
Hours Rated:	50000H	Material:	Glass
Color Temperature:	4000K		
CRI:	82CRI		
Lumen Output:	1150L		

### DIMENSIONS

MOL:	23.78"
MOD:	1.1"
Weight:	0.24

### LISTINGS

Safety Listing:	cULus - Classified; cRUus - Recognized Component
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PLJEL9MNMHK5
DLC Primary Use:	Internal Driver/Line Voltage (UL Type B) Lamps
UL File Listing:	US/CN - E356817; US/CN - E335148
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

### PACKAGING

Each UPC:	045923399022	Case UPC:	10045923399029
Each Quantity:	1	Case Quantity:	25
Each Dimensions:	24.00 x 1.10 x 1.10"	Case Dimensions:	25.00 x 6.00 x 6.00"
1	on Centers	National Toll-Free	Copyright 2024
Brentwood, NY 11717	New York, Florida,	800-43-SATCO	Satco Products, Inc.
PH 631-243-2022	Texas, Washington,	(800-437-2826)	All Rights Reserved
FX 631-243-2027	California, Puerto Rico	www.satco.com	April 29, 2024