



S39903

9T8/LED/24-850/BP/SE-DE

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	9W
Color Temperature:	5000K
Length:	23.78"
Base:	Medium Bi Pin



TECHNICAL SPECIFICATIONS

Wattage:	9W	Beam Spread:	210D
Volts:	120V-277V	Power Factor:	0.9
Incandescent Equivalent:	40W	Operating Temp:	-20C (-4F) to +45C (+113F)
Fluorescent Equivalent:	17W	Ballasting Requirements:	Ballast Bypass
Shape:	T8	Bypass / Direct:	Ballast Bypass
Filament:	LED	Ballast Type:	Type B
Base:	Medium Bi Pin	Single / Dual End:	Single Ended; Double Ended
ANSI Base:	G13	Tube Guard Use:	Approved for use with tube guards
Finish:	Gloss White	Safety Listing:	cULus - Classified; cRUus - Recognized Component
Housing Color:	White	Technology:	LED
Hours Rated:	50000H	Material:	Glass
Color Temperature:	5000K		
CRI:	82CRI		
Lumen Output:	1150L		

DIMENSIONS

MOL:	23.78"
MOD:	1.1"
Weight:	0.24

LISTINGS

Safety Listing:	cULus - Classified; cRUus - Recognized Component
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PLW693BXL7H7
DLC Primary Use:	Internal Driver/Line Voltage (UL Type B) Lamps
UL File Listing:	CN - E356817; US/CN - E335148
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923399039	Case UPC:	10045923399036
Each Quantity:	1	Case Quantity:	25
Each Dimensions:	24.00 x 1.10 x 1.10"	Case Dimensions:	25.00 x 6.00 x 6.00"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2024
Satco Products, Inc.
All Rights Reserved
April 27, 2024