



S39905

17T8/LED/48-835/BP/SE-DE

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	17W
Color Temperature:	3500K
Length:	47.78"
Base:	Medium Bi Pin



TECHNICAL SPECIFICATIONS

Wattage:	17W	Beam Spread:	210D
Volts:	120V-277V	Power Factor:	0.9
Incandescent Equivalent:	90W	Operating Temp:	-20C (-4F) to +45C (+113F)
Fluorescent Equivalent:	45W	Ballasting Requirements:	Ballast Bypass
Shape:	T8	Bypass / Direct:	Ballast Bypass
Filament:	LED	Ballast Type:	Type B
Base:	Medium Bi Pin	Single / Dual End:	Single Ended; Double Ended
ANSI Base:	G13	Tube Guard Use:	Approved for use with tube guards
Finish:	Gloss White	Safety Listing:	cULus - Classified; cRUus - Recognized Component
Housing Color:	White	Technology:	LED
Hours Rated:	50000H	Material:	Glass
Color Temperature:	3500K		
CRI:	82CRI		
Lumen Output:	2100L		

DIMENSIONS

MOL:	47.78"
MOD:	1.1"
Weight:	0.44

LISTINGS

Safety Listing:	cULus - Classified; cRUus - Recognized Component
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PLPOXR8SWHON
DLC Primary Use:	Internal Driver/Line Voltage (UL Type B) Lamps
UL File Listing:	CN - E356817; US/CN - E335148
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923399053	Case UPC:	10045923399050
Each Quantity:	1	Case Quantity:	25
Each Dimensions:	48.00 x 1.10 x 1.10"	Case Dimensions:	49.00 x 6.00 x 6.00"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2024
Satco Products, Inc.
All Rights Reserved
April 29, 2024