



S9620

9.5BR30/LED/2700K/750L/120V/D

GENERAL SPECIFICATIONS

Shape:	BR30
Wattage:	9.5W
Lumen Output:	750L
Color Temperature:	2700K
Base:	Medium
Beam Spread:	105D



TECHNICAL SPECIFICATIONS

Wattage:	9.5W	Color Temperature:	2700K
Volts:	120V	CRI:	80CRI
Incandescent Equivalent:	65W	Lumen Output:	750L
Shape:	BR30	CBCP:	260
Filament:	LED	Dimmable:	Yes-Dimmable
Base:	Medium	Beam Spread:	105D
ANSI Base:	E26	Power Factor:	0.91
Finish:	Frost	Operating Temp:	-25C (-13F) to +45C (+113F)
Housing Color:	Gray	Enclosure Rating:	Open Rated Lamp
Hours Rated:	25000H	Safety Listing:	cULus - Listed
Beam Spread:	105D	Technology:	LED

DIMENSIONS

MOL:	5.157"
MOD:	3.74"
Weight:	0.2

LISTINGS

ES Lamp Category:	Directional
Safety Listing:	cULus - Listed
Location Rating:	Damp
Energy Star:	Yes
ES Unique ID:	ESID-2275527
UL File Listing:	US/CN - E335148
Title 20:	No
CEC Terse:	Non-Compliant
CEC Alt Sub:	S9625
RoHS Compliant:	Yes
FCC Compliant:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923096204	Inner UPC:	20045923096208	Case UPC:	10045923096201
Each Quantity:	1	Inner Quantity:	6	Case Quantity:	12
Each Dimensions:	3.86 x 3.86 x 5.51"	Inner Dimensions:	12.13 x 8.11 x 5.91"	Case Dimensions:	17.13 x 12.72 x 7.01"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2024
Satco Products, Inc.
All Rights Reserved
April 28, 2024

Brand	Model #
Lutron	HW-RPM-4A-120
Lutron	HW-RPM-4U-120
Lutron	LECL-153P
Lutron	MA-PRO
Lutron	MACL-153M
Lutron	MACL-LFQ
Lutron	MRF2S-6ELV
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	NTRP-250
Lutron	PHPM-WBX-DV
Satco	S11268
Satco	86/103

110 Heartland Blvd.
 Brentwood, NY 11717
 PH 631-243-2022
 FX 631-243-2027

Distribution Centers
 New York, Florida,
 Texas, Washington,
 California, Puerto Rico

National Toll-Free
 800-43-SATCO
 (800-437-2826)
www.satco.com

Copyright 2024
 Satco Products, Inc.
 All Rights Reserved
 April 28, 2024