



S9926

12T8/LED/36-830/BP 120-277V

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	12W
Color Temperature:	3000K
Length:	36"
Base:	Medium Bi Pin



TECHNICAL SPECIFICATIONS

Wattage:	12W
Volts:	120V-277V
Incandescent Equivalent:	60W
Fluorescent Equivalent:	25W
Shape:	T8
Filament:	LED
Base:	Medium Bi Pin
ANSI Base:	G13
Finish:	Frost
Hours Rated:	50000H
Color Temperature:	3000K
CRI:	82CRI
Lumen Output:	1400L

Dimmable:	Non-Dimmable
Beam Spread:	220D
Operating Temp:	-20C (-4F) to +45C (+113F)
Ballasting Requirements:	Ballast Bypass
Bypass / Direct:	Ballast Bypass
Ballast Type:	Type B
Safety Listing:	cULus - Classified; cULus - Certified
Technology:	LED

DIMENSIONS

MOL:	36"
MOD:	1"

LISTINGS

Safety Listing:	cULus - Classified; cULus - Certified
Location Rating:	Damp
Energy Star:	No
DLC Approved:	No
UL File Listing:	US/CN - E356817
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923099267
Each Quantity:	1
Each Dimensions:	35.70 x 1.00 x 1.00"

Case UPC:	10045923099264
Case Quantity:	10
Case Dimensions:	36.40 x 6.30 x 3.00"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2024
Satco Products, Inc.
All Rights Reserved
December 22, 2024