



S9930

15T8U6/LED/22.5-830/BP

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	15W
Color Temperature:	3000K
Length:	22.5"
Base:	Medium Bi Pin



TECHNICAL SPECIFICATIONS

Wattage:	15W	Dimmable:	Non-Dimmable
Volts:	120V-277V	Beam Spread:	220D
Incandescent Equivalent:	100W	Power Factor:	0.9
Fluorescent Equivalent:	36W	Operating Temp:	-20C (-4F) to +45C (+113F)
Shape:	T8	Ballasting Requirements:	Ballast Bypass
Filament:	LED	Bypass / Direct:	Ballast Bypass
Base:	Medium Bi Pin	Ballast Type:	Type B
ANSI Base:	G13	Single / Dual End:	Single Ended
Finish:	Frost	Safety Listing:	cULus - Classified; cULus - Certified
Hours Rated:	50000H	Technology:	LED
Color Temperature:	3000K		
CRI:	82CRI		
Lumen Output:	1800L		

DIMENSIONS

MOL:	22.5"
MOD:	1"
Leg Spacing:	6

LISTINGS

Safety Listing:	cULus - Classified; cULus - Certified
Location Rating:	Damp
Energy Star:	No
DLC Approved:	No
UL File Listing:	US/CN - E356817
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923099304	Case UPC:	10045923099301
Each Quantity:	1	Case Quantity:	12
Each Dimensions:	1.40 x 7.50 x 23.20"	Case Dimensions:	24.00 x 15.80 x 9.50"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2024
Satco Products, Inc.
All Rights Reserved
December 22, 2024