



## S9938

11.5T8/LED/48-830/DR-DM

### GENERAL SPECIFICATIONS

|                    |               |
|--------------------|---------------|
| Shape:             | T8            |
| Wattage:           | 11.5W         |
| Color Temperature: | 3000K         |
| Length:            | 48"           |
| Base:              | Medium Bi Pin |



### TECHNICAL SPECIFICATIONS

|                          |               |
|--------------------------|---------------|
| Wattage:                 | 11.5W         |
| Incandescent Equivalent: | 60W           |
| Fluorescent Equivalent:  | 25W-32W       |
| Shape:                   | T8            |
| Filament:                | LED           |
| Base:                    | Medium Bi Pin |
| ANSI Base:               | G13           |
| Finish:                  | Gloss White   |
| Hours Rated:             | 50000H        |
| Color Temperature:       | 3000K         |
| CRI:                     | 82CRI         |
| Lumen Output:            | 1700L         |

|                          |                                                                                                                                                    |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| Dimmable:                | Yes-Dimmable                                                                                                                                       |
| Dimming Function:        | Only in Type A mode; Check Ballast MFG for Dimmer Compatibility                                                                                    |
| Beam Spread:             | 220D                                                                                                                                               |
| Power Factor:            | 0.96                                                                                                                                               |
| Operating Temp:          | -20C (-4F) to +45C (+113F)                                                                                                                         |
| Ballasting Requirements: | May not be compatible with all rapid start ballasts; Direct Replacement-for use on Instant Startand Rapid Start ballasts with no rewiring required |
| Ballast Type:            | Type A                                                                                                                                             |
| Safety Listing:          | cULus                                                                                                                                              |
| Technology:              | LED                                                                                                                                                |

### DIMENSIONS

|      |     |
|------|-----|
| MOL: | 48" |
| MOD: | 1"  |

### LISTINGS

|                  |                               |
|------------------|-------------------------------|
| Safety Listing:  | cULus                         |
| Location Rating: | Damp                          |
| Energy Star:     | No                            |
| DLC Approved:    | No                            |
| UL File Listing: | US/CN E335148                 |
| CEC Terse:       | Lawful for sale in California |
| RoHS Compliant:  | Yes                           |
| FCC Compliant:   | Yes                           |
| NSF Approved:    | Yes                           |
| SDS Class:       | LED_Lamp                      |

### PACKAGING

|                  |                      |
|------------------|----------------------|
| Each UPC:        | 045923099380         |
| Each Quantity:   | 1                    |
| Each Dimensions: | 47.70 x 1.00 x 1.00" |

|                  |                      |
|------------------|----------------------|
| Case UPC:        | 10045923099387       |
| Case Quantity:   | 10                   |
| Case Dimensions: | 48.40 x 6.30 x 3.00" |

110 Heartland Blvd.  
Brentwood, NY 11717  
PH 631-243-2022  
FX 631-243-2027

Distribution Centers  
New York, Florida,  
Texas, Washington,  
California, Puerto Rico

National Toll-Free  
800-43-SATCO  
(800-437-2826)  
www.satco.com

Copyright 2024  
Satco Products, Inc.  
All Rights Reserved  
April 27, 2024