



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11296 - 15 Watt; LED Gimbaled Downlight; 6 Inch; RGB & Tunable White; Round; Starfish IOT; Black Finish; 1200 Lumens; 120-277 Volt

- Air Tight
- Has Driver
- IOT Enabled
- CCT Selectable
- IC Rated



ELECTRICAL

Technology:	LED
Watts:	15W
Volts:	120V-277V
Lumens:	1200L
CRI:	90+
CCT (Kelvins):	2700K-5000K - Warm to Cool White/Color Changeable
Beam Spread :	36
Hours Rated:	50000
Dimmable:	Yes-Dimmable - Only with Starfish App
Dimmable Down To %:	100 to 10 percent
Incandescent Equivalent :	75W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Replaceable Light Source :	No
Connection:	Direct Wired
Power Factor :	>0.9
Voltage Type:	Range Voltage
Warranty:	5 Year Limited - Fixtures

PACKAGING

Each UPC:	045923112966
Each Quantity:	1
Each Dimensions:	8.19 x 3.94 x 8.27

INFO

Specification Note: _____ 360 degree rotation; 0 to 80 degree aiming angle

PHYSICAL

Finish:	Black
Lens Finish:	Frost
Lens Material:	Plastic
Dimensions:	H:2.13" DIA:7.48"
Weight (Lbs.):	1.22
Material:	Aluminum

INSTALLATION

Ceiling Aperture:	6.313 in. Cutout
Max Drywall Thickness:	1 in.
Rec. Spacing Between Fixtures:	3 ft. to 4 ft.
Clearance Height:	3









IOT

IOT Enabled:	Yes
Communication Protocol:	WiFi-2.4GHz
What's Supported:	Google Home; Alexa; Siri; SmartThings
Software Supported:	Tuya/Starfish APP

COMPLIANCE

Safety Listing:	cETLus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
Energy Star Qualified:	No
DLC Approved:	No
CA Prop 65:	Lead
BAA Compliant:	No
FCC Compliant:	Yes
IP Rating:	IP42
RoHS Compliant:	Yes
Restrictions:	No Restrictions

ACCESSORIES

	80-866	6-Inch Asymmetric New Construction Recessed Downlight Mounting Plate; Flat
	80-867	Universal New Construction Recessed Downlight Mounting Plate; Flat; 3,5-Inch; 4-Inch; 6-Inch; 8-Inch
	80-944	New Construction Mounting Plate with Hanger Bars for T-Grid or Stud/ Joist mounting of 6-inch Recessed Downlights; Up to 6.25-inch hole diameter
	80-949	6 FOOT REMOTE DRIVER 1-PIN EXT
	80-952	New Construction Mounting Plate for Stud/ Joist mounting of 6-inch Recessed Downlights; Up to 6,5-inch hole diameter
	80-997	Downlight Hanger Bar Kit; For Asymmetrical Plates; New Construction
	86-216	Temporary work light; LED; For use with remote drivers; Low voltage 10W/12W/24W; 3000K; 12 Volts
	S11282	Remote for Starfish Lighting; White Finish