



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11560 - 9 Watt; LED Direct Wire; Low Profile Downlight; 4 Inch Round; Starfish IOT; Tunable White and RGB; 120 Volt; 90 CRI; White Finish

- Air Tight
- Has Driver
- IOT Enabled
- CCT Selectable
- IC Rated



ELECTRICAL

Technology:	LED
Watts:	9W
Volts:	120V
Lumens:	540L
CRI:	90
Rg Value :	89
CCT (Kelvins):	2000K-5000K - Warm to Cool White/Color Changeable
Beam Spread :	110
Hours Rated:	50000
Dimmable:	Yes-Dimmable - Only with Starfish App
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Smart-Starfish App only
Incandescent Equivalent :	45W
Operating Temperature :	-20C (-4F) to +40C (+104F)
Replaceable Light Source :	No
Connection:	Direct Wired
THD:	<30%
Power Factor :	>0.9
Warranty:	5 Year Limited - Fixtures

PACKAGING

Each UPC:	045923115608
Each Quantity:	1
Each Dimensions:	5.78 x 3.35 x 5.31

PHYSICAL

Finish:	White
Lens Finish:	Frosted
Lens Material:	Polycarbonate (PC)
Dimensions:	H:1.00" DIA:5.00"
Weight (Lbs.):	0.88
Material:	Aluminum

INSTALLATION

Ceiling Aperture:	4.25 in. Cutout
Max Drywall Thickness:	1 in.
Clearance Height:	1

IOT

IOT Enabled:	Yes
Communication Protocol:	WiFi-2.4GHz
What's Supported:	Google Home; Alexa; Siri; SmartThings
Software Supported:	Tuya/Starfish APP

COMPLIANCE

Safety Listing:	cETLus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	ESID-2494955
Energy Star Lamp Category:	Downlight Recessed
DLC Approved:	No
CA Prop 65:	Lead
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

INFO

Installation Note:	Driver Dimensions: 3.46 Inches Long x 3.46 Inches Wide x 1.44 Inches High
--------------------	---

ACCESSORIES

**80-943**

New Construction Mounting Plate with Hanger Bars for T-Grid or Stud/Joist mounting of 4-inch Recessed Downlights; Up to 4.25-inch hole diameter

**80-946**

4" Goof Ring for Remote Driver Installation

**80-950**

New Construction Mounting Plate for Stud/Joist mounting of 4-inch Recessed Downlights; Up to 4.563-inch hole diameter

**80-973**

Emergency Driver Enclosure; For use with S8000 and S8002

**80-986**

6 Foot Remote Driver Extension Cable; 2-Pin; White Finish

**80-987**

Emergency Remote Test Switch; Single Gang Plate; White Finish

**S8000**

5 Watt LED Emergency Driver; 120-277 Volts

**S8002**10 Watt LED Emergency Driver; 120-277 Volt
