



Project/Job Name: \_\_\_\_\_  
 Location: \_\_\_\_\_  
 Fixture Type: \_\_\_\_\_  
 Notes: \_\_\_\_\_

**S21406** - 16 Watt LED PL 4-Pin; 4000K; 1850 Lumens; G24q base; 50000 Average rated hours; Vertical; Type A; Ballast dependent



**ELECTRICAL**

Technology:	LED
Watts:	16W
Volts:	Ballast Dependent
Lumens:	1850L
CRI:	80+
CCT (Kelvins):	4000K - Cool White
Beam Spread :	110
Hours Rated:	50000
Fluorescent Equivalent :	42W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast required, check compatibility
Lamp Ballast Type A/B/C :	Type A
Operating Position:	Base Up or Down
THD:	20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	Ballast Dependent
Warranty:	5-Years

**PACKAGING**

Each UPC:	045923224065
Each Quantity:	1
Each Dimensions:	3.86 x 3.86 x 6.30

**PHYSICAL**

Base:	G24q (4-Pin)
Shape:	PL
Finish:	Frost
Dimensions (In.):	MOL: 5.19 - MOD: 3.75
Weight (Lbs.):	0.33
Housing Color:	White

**COMPLIANCE**

Safety Listing:	cULus
Location Rating:	Damp
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PL6XW9MM7NP1
BAA Compliant:	No
NOM Certificate No.:	NTEC21ENM001000!NTEC21ENM001000-FR1
NOM Expiration Date:	1/18/2023
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions