



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S33113 - 60/80/100 Wattage Selectable; LED; Hi-Bay; Type B; Ballast Bypass; Mogul Extended; 5000K; 100V-277V; 250W-300W Metal Halide Replacement

- Wattage Selectable



ELECTRICAL

Technology:	LED
Watts:	60W/80W/100W
Volts:	120V-277V
Lumens:	8400L/11220L/14000L
CRI:	80+
R9 Value :	12
CCT (Kelvins):	5000K - Natural Light
Beam Spread :	120
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Incandescent Equivalent :	250W/320W/400W
HID Equivalent :	175W/250W/320W
Operating Temperature :	-25C (-13F) to +50C (+122F)
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
Surge Protection :	Built-in surge protection - 4KV
Power Factor :	0.99
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923331138
Each Quantity:	1
Each Dimensions:	5.91 x 5.91 x 11.14

INFO

Installation Note:	Not for use in vapor tight fixtures.
Min Compartment Size:	Length: 15.75 in. Width: 14.96 in.

PHYSICAL

Base:	Mogul Extended
Shape:	Corncob
Finish:	White
Dimensions (In.):	MOL: 9.13 - MOD: 5.51
Weight (Lbs.):	2.68
Material:	Aluminum / Plastic
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor; Outdoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Both
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP64
RoHS Compliant:	Yes
Restrictions:	No Restrictions