



Project/Job Name: \_\_\_\_\_  
 Location: \_\_\_\_\_  
 Fixture Type: \_\_\_\_\_  
 Notes: \_\_\_\_\_

**S9553** - 3W; LED MR16 LED; 5000K; 40 deg. beam spread; GU5.3 base; 12 Volt AC/DC



**ELECTRICAL**

Technology:	LED
Watts:	3W
Volts:	12V
Lumens:	330L
CRI:	80+
CCT (Kelvins):	5000K - Natural Light
Beam Spread :	40
Hours Rated:	25000
Dimmable:	Yes-Dimmable - Forward Phase or Reverse Phase or Phase Selectable; Check the transformer/driver MFG for dimmer compatibility
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Phase Cut; Check the transformer/driver MFG for dimmer compatibility
Incandescent Equivalent :	20W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Light Source:	LED
Voltage Type:	AC/DC
Warranty:	5-Years

**PHYSICAL**

Base:	Bi Pin GU5.3
Shape:	MR16
Finish:	Clear
Lens Finish:	Clear
Dimensions (In.):	MOL: 2 - MOD: 2
Weight (Lbs.):	0.08
Housing Color:	Clear
Lensed:	Lensed Lamp

**COMPLIANCE**

Safety Listing:	cULus
Location Rating:	Damp
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	ANC2101J00000796
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

**PACKAGING**

Each UPC:	045923095535
Each Quantity:	1
Each Dimensions:	2.00 x 2.00 x 2.00

**INFO**

ROI Category:	Screw
---------------	-------



**S9553** - 3W; LED MR16 LED; 5000K; 40 deg. beam spread; GU5.3 base; 12 Volt AC/DC

**DIMMER COMPATIBILITY**

---

**Lutron** CTRP-253P

---

**Lutron** DVLV-600P

---

**Lutron** MA-PRO

---

**Lutron** MALV-600

---

**Lutron** NTRP-250

---

**Lutron** SLV-600P

---